



# TENWOLDE

## Hydraulic Waterfall Anchor / Mooring winch 2 drums

**TTR Code no. : 15.023 + 15.024**

**Specifications :**

Make : Bodewes

Line pull 1<sup>st</sup> layer : 18 tn – 250 bar  
8,2 tn – full drum

Line speed 1<sup>st</sup> layer : 0 - 15 m/min – 140 ltr/min  
0 – 32 m/min – full drum

**Drum size :**

Drum diameter : 500 mm

Drum length : 800 mm

Flange diameter : 1200 mm

Wire Capacity : 650 mtr. steel wire 32 mm (11 layers)

**Drive :**

Hydraulic motor : Linde BMF 105

Gear reduction : 140

**Dimensions :**

Dimensions o.a. : L x W x H= 2650 x 2500 x 1800 mm

Dim. Base frame : L x W = 2300 x 2130 mm

Weight : approx. 7500 kg  
(excl. steel wire)

**Marine Treatment :**

Inorganic zinc over sandblasted frame and guards with finish coats of marine epoxy on entire machine.

**General :**

Hand operated ban brake on drums

Hand operated clutches

Hand operated steering valve on winch

Warping head

1 x left hand / 1 x right hand

No details guaranteed, but believed correct.



**Tenwolde Transport  
en Repair B.V.**  
P.O. Box 5023  
3274 ZJ Heinoord  
Boonsweg 19  
3274 LH Heinoord  
The Netherlands  
T +31-(0) 186-603333  
F +31-(0) 186-603619  
E [info@tenwolde.com](mailto:info@tenwolde.com)

[www.tenwolde.com](http://www.tenwolde.com)