



Plumett Diesel / Hydraulic Capstan Winch – 2 pcs.

TTR Code no. : 15.027 + 15.028

Specifications :

Make : Plumett / VSH
Type : diesel/ hydr. continuous capstan winch TL40

Line Pull : 0 - 5 ton continuous
Line Speed : 0 - 8 m/min (double work)
: 0 - 60 m/min (single work)

Drum size :

Drum diameter : 250 mm
Drum length : 300 mm
Flange dia. : 160 mm

Wire capacity : appr. 280 mtr. steel wire Ø 14 mm

Drive :

Diesel engine : Hatz 2L31C/ 3000 rpm
: 18 Kw – silenced
: Electrical start
Hydro pump : Volvo F11-10/ 29,5 ltr/min
: 3000 rpm
Hydro engine : Volvo F11-19/ 1500 rpm
: 29,5 ltr/min

Dimensions :

Dimensions o.a. : 1350 x 1400 x 1600 mm
(LxWxH)
Weight : approx 1600 kg

General :

- With lifting frame and cover
- Hydraulic tank capacity 125 ltr.
- Operated with a Danfoss PVG32 hand operated prop. 4/3 valve with load sensing
- Safety valve traction setting 80-400 bar
- Dr. Brandt GmbH Tension measurement consisting of: - measurement axis type LB 55/15
- measuring amplifier DDZ-1 SP

