



TENWOLDE

Hydraulic 2 drum anchor/ mooring winch

TTR Code no. : 15.059 + 15.060

Specifications :

Type : AHW 2 SBS
NO. : WO. 3946 + 3963

Line pull 1st layer : 40 tn - 289 bar
25 tn – full drum
Line speed 1st layer : 0 – 20 m/min - 345 ltr/min)
0 – 28 m/min – full drum

Drum size :

Drum diameter : 1067 mm
Drum length : 610 mm
Flange diameter : 1840 mm

Wire capacity : 505 mtr steel wire Ø 44 mm (9 layers)

Drive :

Hydraulic motor : Mannesmann Rextroth
A2F500
Gear reduction : 117,5

Dimensions :

Dimensions o.a. : 5000 x 2800 x 2330 mm
(L x W x H)
Dim. base frame : 5000 x 2618 mm (LxW)
Weight : approx. 15.500 kg
(excl. steel wire)

General :

Pneumatic operated band brake on drums, Pawl and Clutches hand operated hydraulic steering valve on winch



**Tenwolde Transport
en Repair B.V.**
P.O. Box 5023
3274 ZJ Heinenoord
Boonsweg 19
3274 LH Heinenoord
The Netherlands
T +31-(0) 186-603333
F +31-(0) 186-603619
E info@tenwolde.com

No details guaranteed, but believed correct.

www.tenwolde.com